

RF CONNECTOR

Features

Comply with : JIS C-5973, IEC Telecordia

High stable mating and demating characteristic

Low insertion loss and high return loss

Design for Variable cable

Customize assembly

1.6/5.6

1.6/5.6 Straight Clamp
Female1.6/5.6 Straight Clamp
Male1.6/5.6 Straight Crimp
Female1.6/5.6 Straight Crimp
MaleRight Angle 1.6/5.6
Male1.6/5.6 Right Angle
Clamp Female1.6/5.6 T Type
Male-Female1.6/5.6 T Type
Male-Male1.6/5.6 T-type
Female-FemaleY Link Connector
Bulkhead NormalU Link Connector
Male-Male

N Type

N Type Straight
Crimp FemaleN Type Straight Crimp
MaleN Type Straight Clamp
MaleN Type Right Angle
CrimpN Type Right Angle
ClampN Straight Adapter
Clamp FemaleN Right Angle Adapter
TNC Male to N FemaleN Right Angle Adapter
Male to Female

SMB

SMB Straight
Crimp FemaleSMB Right Angle
Crimp Male

SMB Straight Male

1.0/2.3



1.0/2.3 Straight Female



1.0/2.3 Straight Male



T-43 Straight Female

TNC

TNC Right Angle
Crimp FemaleTNC Right Angle
Clamp Female

TNC Straight Crimp



TNC Straight Clamp